

# AF ALUMA FAB METAL SALES, LLC

Panels Systems		Thickness	Faces	Finishes	Texture	Widths	Length	Core Material	R-Value
<b>Column Covers</b>	AF-1000 Caulked Joint	.125, or .090 3, 4, & 6mm  16 Ga.	Aluminum ACM	70% Kynar 500 Coating Anodized Finishes	Smooth	8" Diameter Minimum	15'-0" Maximum	N/A	N/A
			Stainless Steel	Brushed - Polished					
	AF-2000 Hairline Joint	.125, .090 3, 4, & 6mm  16 Ga.	Aluminum ACM	70% Kynar 500 Coating Anodized Finishes	Smooth	8" Diameter Minimum	15'-0" Maximum	N/A	N/A
			Stainless Steel	Brushed - Polished					
<b>Aluminum Plate Caulked Plate System</b>	AP-1000	.125, .090  16 Ga. or 18 Ga.	Aluminum	70% Kynar 500 Coating Anodized Finishes	Smooth	4'-6" Maximum	15'-10" Maximum	N/A N/A	N/A N/A
			Stainless Steel	Brushed - Polished					
<b>Aluminum Composite ACM Fully Caulked Joints Dry Joint ACM</b>	ACM-1000	3mm	Aluminum .020	Kynar 500 Coatings Anodized Finishes	Smooth	5'-0" Maximum	15'-10" Maximum	Standard Polyethelene	N/A
	ACM-2000	4mm 6mm						Fire Rated	
<b>Laminated Panels Glazed-in Panels Curtainwall Panels</b>	HC-1000	1" - 6"	Aluminum .040-.125	70% Kynar 500 Coatings Anodized Finishes	Smooth or Embossed	4'-6" Maximum	24'-0" Maximum	Kraftpaper Honeycomb Aluminum Honeycomb	N/A N/A
			Galvanized Steel 22 Ga.& 20 Ga.	70% Kynar 500 Coatings					
			Stainless Steel	Brushed - Polished					
	FM-1000	1" - 6"	Aluminum .040-.125	70% Kynar 500 Coatings Anodized Finishes	Smooth or Embossed	4'-6" Maximum	24'-0" Maximum	Polyisocyanurate	R = 5.4 per inch
			Galvanized Steel 22 Ga.& 20 Ga.	70% Kynar 500 Coatings				EPS Expanded Polysyrene	R = 5 per inch
			Stainless Steel	Brushed - Polished					
<b>Custom Fabrication Flashings Brake-metal</b>			Aluminum .040-.125	70% Kynar 500 Coatings Anodized Finishes	N/A				N/A
			Galvanized Steel 22 Ga.& 20 Ga.	70% Kynar 500 Coatings					N/A
			Stainless Steel	Brushed - Polished					
<b>Sunscreens Extruded Sunscreens Airfoil - Tube - Custom</b>			Aluminum	70% Kynar 500 Coatings Anodized Finishes	N/A				N/A N/A